

**(19) World Intellectual Property Organization
International Bureau**



(43) International Publication Date
3 January 2003 (03.01.2003)

(10) International Publication Number
WO 03/001075 A1

PCT

- (51) **International Patent Classification⁷:** **F16B 19/12** (74) **Agents:** BROCK, Christopher, M. et al.; Harness, Dickey & Pierce, P.L.C., P.O. Box 828, Bloomfield Hills, MI 48303 (US).

(21) **International Application Number:** PCT/US02/19627

(22) **International Filing Date:** 21 June 2002 (21.06.2002) (81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:**
60/299,950 21 June 2001 (21.06.2001) US

(71) **Applicant (for all designated States except US):** BLACK & DECKER, INC. [US/US]; 1423 Kirkwood Highway, Newark, DE 19805 (US).

(72) **Inventors; and**

(75) **Inventors/Applicants (for US only):** O'BANION, Michael [US/US]; 1230 Canon Way, Westminster, MD 21157 (US). SAUERWEIN, William [US/US]; 4122 Cremson Drive, Phoenix, MD 21131 (US).

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM; AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Declaration under Rule 4.17:
— of inventorship (Rule 4.17(iv)) for US only

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

- (54) Title:** EXPLOSIVE ASSISTED EXPANDING FASTENER



(57) **Abstract:** An explosive assisted fastener (20) is provided for joining steel framing members (12, 14, 16). The fastener (20) is comprised of an integrally formed member having a head section (22), a stem section (24) and a tip section (26), such that the head section (22) is disposed at a first end of the stem section (24) and adapted to be linearly driven by a driving device into the framing members, and the tip section (26) is disposed at a distal second end of the stem section (24) and adapted to penetrate the framing members. The fastener (20) further includes an explosive material embedded in the tip section (26) of the fastener. In operation, the fastener (20) is driven through the framing members until the head section (22) of the fastener seats against an outer surface of the framing members. Once driven into place, the explosive material (28) residing in the fastener is detonated, thereby radially expanding the tip section (26) of the fastener and preventing removal of the fastener from the framing members.

WO 03/001075 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

EXPLOSIVE ASSISTED EXPANDING FASTENER

Cross-Reference to Related Applications

5 **[0001]** This application claims the benefit of U.S. Provisional Application No. 60/299,950, filed June 21, 2001.

Background of the Invention

10 **[0002]** The present invention relates generally to steel framing and, more particularly, to an improved cost-effective method for fastening steel framing.

15 **[0003]** Steel framing is revolutionizing the construction industry. Steel is a high quality framing material that will not shrink, warp, or attract termites and other wood boring insects. In recent years, the price of steel has become more competitive with wood and other construction materials. However, despite its advantages, steel framing has not become prevalent in the residential construction industry. The lack of a quick and cost effective technique for fastening steel members has prevented steel framing from emerging as the predominant building material in residential construction.

20 **[0004]** Therefore, it is desirable to provide a quick and cost-effective technique for fastening steel members. It is envisioned that the steel fastening technique will be comparable in speed to an air nailer used to fasten wood materials. It is further envisioned that the steel fastening technique will provide a minimal gap between steel members, a pullout force of at least 216 lb., a shear force of at least 164 lb., as well as cause minimal destruction of any
25 galvanize coating on the steel members.

Summary of the Invention

30 **[0005]** In accordance with the present invention, an explosive-assisted fastener is provided for joining steel framing members. The fastener is comprised of an integrally formed member having a head section, a stem section and a tip section, such that the head section is disposed at a first end of the stem section and adapted to be linearly driven by a driving device into the

framing members, and the tip section is disposed at a distal second end of the stem section and adapted to penetrate the framing members. The fastener further includes an explosive material embedded in the tip section of the fastener. In operation, the fastener is driven through the framing members until
5 the head section of the fastener seats against an outer surface of the framing members. Once driven into place, the explosive material residing in the fastener is detonated, thereby radially expanding the tip section of the fastener and preventing removal of the fastener from the framing members.

[0006] Further areas of applicability of the present invention will
10 become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating the preferred embodiment of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

15 Brief Description of the Drawings

[0007] Figure 1 is a fragmentary prospective view of a steel framing member having two additional steel framing members fastened thereto in accordance with the present invention;

[0008] Figure 2 is a side view of a first preferred embodiment of an
20 explosive assisted fastener in accordance with the present invention;

[0009] Figures 3 and 4 are cross-sectional views, taken along line 5-5 of Figure 1, illustrating the explosive assisted fastener being driven through the steel members in accordance with the present invention;

[0010] Figure 5 is a cross-sectional view, taken along line 5-5 of
25 Figure 1, illustrating detonation of explosive material embedded in the explosive assisted fastener in accordance with the present invention; and

[0011] Figure 6 is a side view of a second preferred embodiment of an explosive assisted fastener in accordance with the present invention;

[0012] Figure 7 is a bottom view of the second preferred embodiment
30 of the explosive assisted fastener in accordance with the present invention;

[0013] Figure 8 is a cross-sectional view, taken along line 5-5 of Figure 1, illustrating the explosive assisted fastener penetrating partially through the steel members in accordance with the present invention;

5 [0014] Figure 9 is a cross-sectional view, taken along line 5-5 of Figure 1, illustrating the explosive assisted fastener being driven against the outer surface of the steel members in accordance with the present invention; and

10 [0015] Figure 10 is a cross-sectional view, taken along line 5-5 of Figure 1, illustrating a pin being driven into a bottom portion of the explosive assisted fastener in accordance with the present invention;

[0016] Figure 11 is a side view of a third preferred embodiment of an explosive assisted fastener in accordance with the present invention;

15 [0017] Figures 12 and 13 are cross-sectional views, taken along line 5-5 of Figure 1, illustrating the explosive assisted fastener being driven through the steel members in accordance with the present invention; and

[0018] Figure 14 is a cross-sectional view, taken along line 5-5 of Figure 1, illustrating detonation of the explosive material embedded in the explosive assisted fastener in accordance with the present invention.

20 Detailed Description of the Preferred Embodiments

[0019] Referring to Figure 1, a fragmentary prospective view of a longitudinal steel framing member 12 having two upright steel framing members 14 and 16 fastened thereto. Each c-shaped framing member includes a bottom wall and two side walls having a thickness in the range from 0.018" to 0.071".
25 Additionally, each steel member may range from 33 ksi to 80 ksi as is well known in the art. As will be more fully described below, one or more fasteners 20 may be used to join the upright steel framing members 14 and 16 to the longitudinal steel framing member 12. While the following description is provided with reference to this particular configuration, it is readily understood
30 that the fastening technique of the present invention is applicable to any two or more adjacent members made of steel (e.g., carbon steel, hardened steel, stainless steel, tool steel, etc.) or other material having similar attributes to

those of steel (e.g., nonferrous metals, including nickel, alloys, titanium, copper and aluminum).

[0020] In accordance with the present invention, one or more explosive assisted fasteners 20 may be used to join the steel members. A first
5 exemplary embodiment of an explosive assisted fastener 20 is depicted in Figure 2. The fastener 20 is comprised of an integrally formed member having a head section 22, a stem section 24 and a tip section 26. The fastener 20 is preferably comprised of a hardened steel material or, alternatively, a softer steel material having a tip section formed of a hardened material such as carbide,
10 ceramic, or a hardened steel. In addition, a small explosive charge 28 is embedded in either the tip section 26 or the stem section 24 of the fastener 20. It is envisioned that barium styphnate, nitro cellulose, or other known explosive materials which are commonly electrically detonated may be used for the explosive charge 28.

[0021] In operation, a two-step process is used to set the fastener 20.
15 First, the fastener 20 is driven into the steel members until the head of the fastener seats against the outer surface of the steel members as shown in Figures 3 and 4. It is readily understood that the driving device is configured to engage the head section 22 of the fastener and may provide a back plate to
20 prevent unwanted deformation of the steel members at the point at which the fastener pierces the steel members. In one embodiment, the driving device drives the fasteners at relatively high speeds (e.g., greater than 50 feet per second). In an alternative embodiment, the driving device may drive the fastener at lower speeds, but apply a relatively high force. One skilled in the art
25 will readily recognize that an air nailer or other known driving devices may be configured to drive the fasteners 20 of the present invention into the steel members.

[0022] Once the fastener 20 is driven into place, the embedded
explosive charge 28 is detonated, thereby outwardly expanding the tip section
30 26 of the fastener 20. Referring to Figure 5, the radially flared tip section 26 engages the underside of the steel members, thereby preventing removal of the fastener from the steel members. To detonate the explosive charge 28, a thin

copper wire or other electrical conducting material 30 may be embedded in the fastener 20. The wire 30 is externally accessible via the head section 22 of the fastener and extends through the stem section 24 to electrically couple to the explosive material 28 embedded in the fastener 20. An external detonating device 32 electrically connected to the wire 30 may be used to detonate the explosive material 28. It is readily understood that the detonating device 32 may be associated with and cooperatively operable with the driving device used to drive the fastener into the steel members

[0023] A second exemplary embodiment of an explosive assisted fastener 20' is depicted in Figure 6. Similarly, the fastener 20' is comprised of an integrally formed member having a head section 22', a stem section 24', a tip section 26', and an embedded explosive material 28'. In this embodiment, the explosive material 28' may be one or many commercially available mechanically denotated materials, such as lead styphate, lead azide or a combination thereof. The fastener 20' is further defined to include a circular bore 30' which is formed in the head section 22' of the fastener 20'. The bore 30' extends downwardly through the stem section 24' and then tapers inwardly to mimic the outer shape of the tip section 26'. As will be more fully explained below, the bore 30' is adapted to receive a pin therein.

[0024] In operation, the expanding fastener 20' is driven into the steel members until the head of the fastener seats against the outer surface of the steel members as shown in Figures 8 and 9. Once the fastener 20 has been driven into place, the embedded explosive material 28' may be mechanically detonated as shown in Figure 10. For instance, a pin 34' may be driven into the bore 30' and into contact with the explosive material 28' residing in the tip section 26' of the fastener. The impact force of the pin 34' detonates the explosive material 28'. It is envisioned that the pin 34' may be integrated into the driving device that drives the fastener 20' into the steel members. In other words, the driving device may be configured to provide a two-step actuator: a first step for driving the fastener into the steel members, and a second step for driving the pin 34' into contact with the explosive material.

[0025] As a result, a portion of the fastener extending beyond the underside of the steel members expands radially outward as best seen in Figure 10. The radially flared portions of the tip section 26' prevents removal of the fastener from the steel members. To facilitate flaring, one or more fracture
5 lines may be formed in the tip section 26' of the fastener 20' as depicted in Figure 7. It is envisioned that the fracture lines may not extend to the distal end of the tip section 26', thereby maintaining the structural integrity of the tip section 26'. It is further envisioned that a plurality of raised ridges 32' may extend outwardly from the outer surface of the stem section 24' to further
10 prevent removal of the fastener from the steel members.

[0026] Alternatively, the explosive material 28' may be detonated upon impact of the fastener with the outer surface of the steel framing members. In this case, the fastener 20 is similarly driven into the steel members until the head section of the fastener seats against the outer surface
15 of the steel members with the fastener 20". Although the explosive material 28' is detonated upon impact of the tip section 26' with the framing members, the burn time of the explosive material 28' is configured such that the outward expansion of the tip section 26' does not occur until it extends beyond the underside of the steel members. As described above, the radially flared
20 portions of the tip section 26' prevents removal of the fastener from the steel members.

[0027] A third exemplary embodiment of an explosive assisted fastener 20" is depicted in Figures 11-14. Referring to Figure 11, the fastener 20" is primarily comprised of an integrally formed member having a head section 22", a stem section 24", a tip section 26", and an embedded explosive
25 material 28". In addition, the fastener 20" includes a circular bore 30" which is formed in the head section 22" of the fastener 20". In this case, the bore 30' extends downwardly into the stem section 24", but does not substantially extend into the tip section 26" of the fastener 20". Thus, the explosive charge
30 28" is embedded in the stem section 24" of the fastener 20". In this embodiment, a plurality of raised ridges 32" extend outwardly from the outer surface of the stem section 24". It is also envisioned that the stem section 24"

may be comprised of a more ductile material than the remainder of the fastener.

[0028] In operation, the explosive assisted fastener 20" is driven into the steel members until the head of the fastener seats against the outer surface of the steel members as shown in Figures 12 and 13. Once the fastener 20 has been driven into place, the embedded explosive charge 28" may be mechanically detonated as shown in Figure 13. Specifically, a pin 34" is driven into the bore 30" and into contact with the explosive material 28", such that the impact force of the pin 34" detonates the explosive material 28". As a result, the outer walls of the stem section 24" (adjacent to the explosion) expand outwardly into the adjacent surface of the framing members as shown in Figure 14. The ridges 32" along the outer surface of the stem section 24" serve as teeth which prevent the removal of the fastener from the steel members.

[0029] While the invention has been described in its presently preferred form, it will be understood that the invention is capable of modification without departing from the spirit of the invention as set forth herein.

CLAIMS

What is claimed is:

1. An explosive assisted fastener for joining framing members,
5 comprising:
an integrally formed member having a head section, a stem section and a tip section, wherein the head section is disposed at a first end of the stem section and adapted to be linearly driven by a driving device into the framing members, and the tip section is disposed at a distal second end of the
10 stem section and adapted to penetrate the framing members; and
an explosive material embedded in the tip section of the fastener.
2. The explosive assisted fastener of Claim 1 further comprises a bore that is formed into the head section and extending through the stem section into the tip section of the fastener, such that the bore is adapted to
15 receive a pin therein for detonating the explosive material residing in the tip section of the fastener.
3. The explosive assisted fastener of Claim 1 wherein the tip section further includes one or more fracture points to facilitate radially outward expansion of the tip section.
- 20 4. The explosive assisted fastener of Claim 1 wherein the stem section is a cylindrical body having a plurality of annular grooves formed in an outer surface of the cylindrical body.
5. The explosive assisted fastener of Claim 1 further comprises a
conductive material embedded in the fastener and electrically connected to the
25 explosive material, thereby enabling detonation of the explosive material.





Figure - 2

27

Figure - 3





Figure - 4

3/7




Figure - 5




Figure - 6

4/7




Figure - 7




Figure - 8




Figure - 9






Figure - 10

6/7



7/7




Figure - 12




Figure - 13

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 02/19627

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F16B19/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 332 311 A (SCHULZ WILLIAM E) 25 July 1967 (1967-07-25)	1,2,5
Y	column 6, line 12 - line 29 figure 5	3,4
Y	DE 369 395 C (FRANK ALLAN) 19 February 1923 (1923-02-19) page 3, left-hand column, line 59 -right-hand column, line 88 claims 5,6 figure 3	3,4

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

2 September 2002

Date of mailing of the international search report

16/09/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Granger, H

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 02/19627

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3332311	A	25-07-1967	NONE
DE 369395	C	19-02-1923	NONE